
RemoDAQ-9431/9831/9438/9838




- 10/100/1000Base-T Ethernet interface
- Self-built Modbus /RTU Server
- Support Modbus /TCP Client
- Support Modbus /RTU Master and Slave Station
- Support Ethernet Isagraf(R-9438/9838)
- IEC-61131-3 Standard
- Support LD / FB/SFC/IL/ST language
- Linux operating system, C language programming(R-9431/9831)
- 4/8 slots for use with I/O, Basic unit can support up to 64/128 of the I/O points
- Support for AI/AO/DI/DO counter function block
- Through a serial port extension 32 extension units, Each extension unit can support 64/128 of the I/O points

Introduction

RemoDAQ-9431/9831/9438/9838 is a soft logic controller with Ethernet interface. It also provides Ethernet function, including the Modbus/TCP Server, Modbus/TCP Client and Ethernet. Then users can facilitate rapid completion based on Ethernet architecture programming.

Specifications



| CDIL | Atmel SAMA5D36 Cortex a5, 536MHz | | |
|------------------------|-------------------------------------------------------|----------------------------------------------------------------------------------------|------------------------------------------|
| • CPU | 512M Nand Flash, 256KB SRAM (Save the data one month) | | |
| • Storage | , , , | | |
| Operating system | Linux | | |
| Real-time clock | enabled | | |
| Built-in watchdog | enabled | | |
| • COM1 | RS-232/485 | | |
| • COM2 | RS-485 | | |
| • COM3 | RS-232 | | |
| • COM4 | RS-232/485 | | |
| communication protocol | Modbus/RTU and Modbus/TCP | | |
| • I/O capacity | 4 slots(9431/9438), 8 slots(9831/9838) | | |
| Status display | Power, CPU, Communication and battery | | |
| CPU power consumption | 3.0W | | |
| Field bus | CAN field, 2 interface, Support 2.0A/2.0B Protocol | | |
| Isolation protection | power input | 3000 VDC | |
| | communication | 2500 VDC(except COM3) | |
| Ethernet | 1*10/100/1000Mbps, | | |
| | 1*10/100Mbps | | |
| VGA display | Resolution | 1024*768 | |
| Extension | Through 485 extensible 32 slave units of 4/8 slots | | |
| 0.5 | · Isagraf Soft logic programming | | |
| Software support | • C language programming | | |
| Power | • Unconditioned +10~+30VDC | | |
| | Reverse power protection | | |
| Mechanical features | Coating | KJW plastics, with install accessories | |
| | Plug-in screw terminator | Plug-in screw terminator: diameter of lead 0.05mm2 to 2.5mm2, 1-#12 or 2-#14 to #22AWG | |
| Environment | Operating temp | -40∼85℃ | |
| | Storage temp | -40∼85℃ | |
| | • Humidity | 5~95 %non-condensing | |
| Order information | • RemoDAQ-9431 | | 4 slots Ethernet programmable controller |
| | • RemoDAQ-9438 | | 4 slots Ethernet programmable controller |
| | • RemoDAQ-9831 | | 8 slots Ethernet soft logic controller |
| | • RemoDAQ-9838 | | 8 slots Ethernet soft logic controller |